



BT12 MOTION SENSOR PAIRING

Service

The BTMotion Sensor may not be paired when arriving from the factory. Follow the procedure below to pair the motion sensor to the control module.

1. If not previously done, download the Carefree Connects Mobile App.
2. Open the app.
3. Tap the Awning Management icon in the upper left corner of the screen. 
4. Using the switches, extend the awning.
5. Remove the motion sensor from the leadrail and remove the batteries from the motion sensor.
6. Pair the awning:
 - 6.1. Retract the awning.
 - 6.2. When the awning stops, press and hold the retract switch for 3-5 seconds, then release.
 - 6.3. On the Management Screen watch for awning to appear under Available Awnings.
7. Insert the batteries back into the BTMotion Sensor.
8. In the app under the Management Screen tap the awning under Available Awnings.
 - 8.1. Add the awning to "My Awnings". You can rename the awning here if desired.
9. Return to the main screen and tap the awning.
 - 9.1. It should read "connecting". When connected, the awning icon will change color.
10. Test the LED light controls. (you must have the LED power switch ON)
11. Tap the "Settings Navigation" icon in the upper right corner. 
12. Scroll to the "Peripherals" page.
13. See if the system has the motion sensor listed. 
14. Does it have a green or red dot next to it or is it not listed.
15. If the dot is green extend the awning and reinstall the motion sensor in the lead rail.
16. Shake the leadrail to see if the leadrail retracts.
17. If the motion sensor is not connected, repeat steps 4 – 16 to ensure no steps were skipped or done incorrectly.